



EVEN BEZEL

Create impressive space for all target audience

Make a powerful and efficient space to achieve your business goals


Even Bezel Screens is a communication tool that help you announce your messages or advertisements with rich visual content in your target audience's living areas through quality broadcasting in a digital environment.



Energy Efficient
Technology




Remote
Control



7/24 Working



Anti - Glare



High
Brightness



Network
Upgrade



Even Bezel Screens create a user-friendly and remote-controlled interactive system, which is distributed through a network and can create broadcast stream featuring special content for companies, services and products!

Promote your corporate image with such detail and excellent visibility

Even Bezel is a good connection way between the target audience and your brand. It helps that you draw visitors attention and deliver messages more effectively with stunning visibility. Also it supports sharing rich visual contents, advertisement and information about anything you want.



Present strikingly messaging with new generation digital solutions

Even Bezel can be easily adapted and developed not only for several applications but also every sectors. It enables interaction with multimedia content, maps, information, advertising posters, websites, videos and more.

PANEL	SE420MA	SE490MA	SE550MA
Panel Size	42"	49"	55"
Panel Type	60Hz ELED	60Hz ELED	60Hz ELED
Resolution	1920 X 1080	1920 X 1080	1920 X 1080
Brightness (Typ.)	500 cd/m ²	500 cd/m ²	500 cd/m ²
Contrast	3000:1 (Typ.) (TM)	3000:1 (Typ.) (TM)	3000:1 (Typ.) (TM)
Viewing Angle (H x V)	178° x 178°	178° x 178°	178° x 178°
Response Angle (G-to-G)	8 ms (G to G)	8 ms (G to G)	8 ms (G to G)
Active Display Area (mm)	927.94 (H) x 521.96 (V)	1073.78 (H) x 604 (V)	1209.6 (H) x 680.4 (V)

CONNECTIVITY			
Video Input	VGA, HDMI, DVI	VGA, HDMI, DVI	VGA, HDMI, DVI
Video Output	N/A	N/A	N/A
Audio Input / Output	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack
USB	N/A	N/A	N/A
External Control	N/A	N/A	N/A

POWER			
Power Type	Internal	Internal	Internal
Power Requirement	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz
Power Consumption	154W	165W	190W
Standby Mode	<0,5W	<0,5W	<0,5W

DIMENSIONS			
Vesa Mount	200 x 200	400 x 400	400 x 100
Frame Width (mm)	959.7 x 550.1 x 29.9	1092.6 x 624.8 x 29.9	1228.4 x 701.2 x 29.9
Package Size (mm)	1037 x 628 x 132	1195 x 721 x 167	1335 x 812 x 182

OPERATION			
Operation Life	7/24 - 50.000 hours	7/24 - 50.000 hours	7/24 - 50.000 hours
Working Conditions	Operation Temp.:0~ 40 °C ; Storage Temp.:20~60 °C	Operation Temp.:0~ 40 °C ; Storage Temp.:20~60 °C	Operation Temp.:0~ 40 °C ; Storage Temp.:20~60 °C
Humidity	10 ~ 80%	10 ~ 80%	10 ~ 80%

CERTIFICATION AND COMPATIBILITY			
Safety	EN60950-1	EN60950-1	EN60950-1
EMC	Class A	Class A	Class A
Environment	ENERGY STAR 6.0 (USA)	ENERGY STAR 6.0 (USA)	ENERGY STAR 6.0 (USA)

OTHER			
Included in Packet	Easy Installation Guide, Warranty Document, Power Cable (Other Accessories Externally)		

PANEL	SE420MB	SE490MB	SE550MB
Panel Size	42"	49"	55"
Panel Type	60Hz ELED	60Hz ELED	60Hz ELED
Resolution	1920 X 1080	1920 X 1080	1920 X 1080
Brightness (Typ.)	500 cd/m ²	500 cd/m ²	500 cd/m ²
Contrast	3000:1 (Typ.) (TM)	3000:1 (Typ.) (TM)	3000:1 (Typ.) (TM)
Viewing Angle (H x V)	178° x 178°	178° x 178°	178° x 178°
Response Angle (G-to-G)	8 ms (G to G)	8 ms (G to G)	8 ms (G to G)
Active Display Area (mm)	927.94 (H) x 521.96 (V)	1073.78 (H) x 604 (V)	1209.6 (H) x 680.4 (V)

CONNECTIVITY			
Video Input	HDMI-1, HDMI-2, DVI, DP	HDMI-1, HDMI-2, DVI, DP	HDMI-1, HDMI-2, DVI, DP
Video Output	N/A	N/A	N/A
Audio Input / Output	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack
USB	N/A	N/A	N/A
External Control	N/A	N/A	N/A

POWER			
Power Type	Internal	Internal	Internal
Power Requirement	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz
Power Consumption	154W	165W	190W
Standby Mode	<0,5W	<0,5W	<0,5W

DIMENSIONS			
Vesa Mount	200 x 200	400 x 400	400 x 100
Frame Width (mm)	959.7 x 550.1 x 29.1	1092.6 x 624.8 x 29.9	1228.4 x 701.2 x 29.9
Package Size (mm)	1038 x 628 x 132	1195 x 721 x 167	1335 x 812 x 182

OPERATION			
Operation Life	7/24 - 50.000 hours	7/24 - 50.000 hours	7/24 - 50.000 hours
Working Conditions	Operation Temp.:0~ 40 °C ; Storage Temp.:20~60 °C	Operation Temp.:0~ 40 °C ; Storage Temp.:20~60 °C	Operation Temp.:0~ 40 °C ; Storage Temp.:20~60 °C
Humidity	10 ~ 80%	10 ~ 80%	10 ~ 80%

CERTIFICATION AND COMPATIBILITY			
Safety	EN60950-1	EN60950-1	EN60950-1
EMC	Class A	Class A	Class A
Environment	ENERGY STAR 6.0 (USA)	ENERGY STAR 6.0 (USA)	ENERGY STAR 6.0 (USA)

OTHER			
Included in Packet	Easy Installation Guide, Warranty Document, Power Cable (Other Accessories Externally)		

PANEL	SE420HA	SE490HA	SE550HA
Panel Size	42"	49"	55"
Panel Type	60Hz ELED	60Hz ELED	60Hz ELED
Resolution	1920 X 1080	1920 X 1080	1920 X 1080
Brightness (Typ.)	700 cd/m ²	700 cd/m ²	700 cd/m ²
Contrast	3000:1 (Typ.) (TM)	3000:1 (Typ.) (TM)	3000:1 (Typ.) (TM)
Viewing Angle (H x V)	178° x 178°	178° x 178°	178° x 178°
Response Angle (G-to-G)	8 ms (G to G)	8 ms (G to G)	8 ms (G to G)
Active Display Area (mm)	927.94 (H) x 521.96 (V)	1073.78 (H) x 604 (V)	1209.6 (H) x 680.4 (V)

CONNECTIVITY			
Video Input	VGA, HDMI, DVI	VGA, HDMI, DVI	VGA, HDMI, DVI
Video Output	N/A	N/A	N/A
Audio Input / Output	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack
USB	N/A	N/A	N/A
External Control	N/A	N/A	N/A

POWER			
Power Type	Internal	Internal	Internal
Power Requirement	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz
Power Consumption	154W	165W	190W
Standby Mode	<0,5W	<0,5W	<0,5W

DIMENSIONS			
Vesa Mount	200 x 200	400 x 400	400 x 100
Frame Width (mm)	959.7 x 550.1 x 29.1	1092.6 x 624.8 x 29.9	1228.4 x 701.2 x 29.9
Package Size (mm)	1039 x 628 x 132	1197 x 721 x 167	1337 x 812 x 182

OPERATION			
Operation Life	7/24 - 50.000 hours	7/24 - 50.000 hours	7/24 - 50.000 hours
Working Conditions	Operation Temp.:0~ 40 °C ; Storage Temp.:20~60 °C	Operation Temp.:0~ 40 °C ; Storage Temp.:20~60 °C	Operation Temp.:0~ 40 °C ; Storage Temp.:20~60 °C
Humidity	10 ~ 80%	10 ~ 80%	10 ~ 80%

CERTIFICATION AND COMPATIBILITY			
Safety	EN60950-1	EN60950-1	EN60950-1
EMC	Class A	Class A	Class A
Environment	ENERGY STAR 6.0 (USA)	ENERGY STAR 6.0 (USA)	ENERGY STAR 6.0 (USA)

OTHER			
Included in Packet	Easy Installation Guide, Warranty Document, Power Cable (Other Accessories Externally)		

PANEL	SE420HB	SE490HB	SE550HB
Panel Size	42"	49"	55"
Panel Type	60Hz ELED	60Hz ELED	60Hz ELED
Resolution	1920 X 1080	1920 X 1080	1920 X 1080
Brightness (Typ.)	700 cd/m ²	700 cd/m ²	700 cd/m ²
Contrast	3000:1 (Typ.) (TM)	3000:1 (Typ.) (TM)	3000:1 (Typ.) (TM)
Viewing Angle (H x V)	178° x 178°	178° x 178°	178° x 178°
Response Angle (G-to-G)	8 ms (G to G)	8 ms (G to G)	8 ms (G to G)
Active Display Area (mm)	927.94 (H) x 521.96 (V)	1073.78 (H) x 604 (V)	1209.6 (H) x 680.4 (V)

CONNECTIVITY			
Video Input	HDMI-1, HDMI-2, DVI, DP	HDMI-1, HDMI-2, DVI, DP	HDMI-1, HDMI-2, DVI, DP
Video Output	N/A	N/A	N/A
Audio Input / Output	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack
USB	N/A	N/A	N/A
External Control	N/A	N/A	N/A

POWER			
Power Type	Internal	Internal	Internal
Power Requirement	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz
Power Consumption	154W	165W	190W
Standby Mode	<0,5W	<0,5W	<0,5W

DIMENSIONS			
Vesa Mount	200 x 200	400 x 400	400 x 100
Frame Width (mm)	959.7 x 550.1 x 29.1	1092.6 x 624.8 x 29.9	1228.4 x 701.2 x 29.9
Package Size (mm)	1040 x 628 x 132	1198 x 721 x 167	1338 x 812 x 182

OPERATION			
Operation Life	7/24 - 50.000 hours	7/24 - 50.000 hours	7/24 - 50.000 hours
Working Conditions	Operation Temp.:0~ 40 °C ; Storage Temp.:20~60 °C	Operation Temp.:0~ 40 °C ; Storage Temp.:20~60 °C	Operation Temp.:0~ 40 °C ; Storage Temp.:20~60 °C
Humidity	10 ~ 80%	10 ~ 80%	10 ~ 80%

CERTIFICATION AND COMPATIBILITY			
Safety	EN60950-1	EN60950-1	EN60950-1
EMC	Class A	Class A	Class A
Environment	ENERGY STAR 6.0 (USA)	ENERGY STAR 6.0 (USA)	ENERGY STAR 6.0 (USA)

OTHER			
Included in Packet	Easy Installation Guide, Warranty Document, Power Cable (Other Accessories Externally)		



unisignds



unisignds



unisignds



unisign

www.unisign.com.tr
info@unisign.com.tr



EVEN BEZEL
